H½2000

Standing flowerbed



Specifications

A side view

Beware of imitations!

It is impossible to copy quality and safety. Only products branded with Terra's sign can provide the highest quality, safety and accuracy of execution.





H1/2

Product protected by patent



Registered design



Made in Europe

Weight before planting

Weight after planting



Warranty 24 months



KG



Terra's Cascading Flower Towers include a 2-year warranty program called "DOOR TO DOOR". In practice it is an extensive system of support and technical assistance, as well as an extremely efficient service guarantee. Product's flaws will promptly be fixed by our service team in any place designated or new products will be delivered.

Colours (DUPLEX)







600 (1200)

Capacity ()

Total height $\stackrel{\triangle}{=}$

Base diameter Ø

Number of rings



9

584 liters

1990 mm

½1200 mm



DUPLEX System

The combination of the zinc coating and a layer of structural polyester powder paint guarantee a resistant protection surface, which durability can be defined as a doubled product of the sum of these two coatings.

Production method

laser-cut rings

rings welded in MAG / TIG technology

all the elements are hot dip zinc coated

powder coated rings (DUPLEX system)

Safety

rubber gasket on each rings

no sharp edges

heavy and stable

high resistance to vandalism

can be fixed to the ground

Copyright © 2013 Terra. All rights reserved.






H½2000

Standing flowerbed










B Side view




2 SETS PACKED IN A BOX


UP TO 8 SETS FOR A EURO PALLET


Set contents


Lower pan with legs	1 item	Mast (profile 50x20 mm)	1 item
Half-rings	8 items	Mast (profile 60x30 mm)	1 item
Conical screw 8x50	4 items	Upper span	3 items
Screw 10x50	14 items	Lower span	3 items
Screw 10x90	4 items	Security flat bar	2 items
Screw 6x20	7 items	Gasket / glue	20m / 2 items

Additional accessories









number of lines in the system: 5

type of connector: GEKA flow of drippers: 2-3 l/h

pressure: 0,5 - 4 atm

opening pressure of the anti-drip: 0,4 atm closing pressure of the anti-drip: 0,2 atm

hose type: **new generation** resistant to chemicals and acidification

Copyright © 2013 Terra. All rights reserved.



