
H2400

Standing flowerbed



Specifications

(mm



Beware of imitations!

It is impossible to copy quality and safety. Only products branded with Terra's sign can provide the highest quality, safety and accuracy of execution.

Product protected by patent



Registered design



Warranty 24 months

1200			`	
Number of rings	12	Weight before planting	(KG	147 kg
Capacity 🖒	1335 liters	Weight after planting	KG KG	> 710 - 1300 kg 🌞
Total height	2610 mm	Estimated amount of seedlings	8	145 - 180 pieces
Base diameter 🖉	1200 mm	Warranty	\bigcirc	24 months

Made in FU

Weight depending on the type of soil and its moisture

Terra's Cascading Flower Towers include a 2-year warranty program called "DOOR TO DOOR". In practice it is an extensive system of support and technical assistance, as well as an extremely efficient service guarantee. Product's flaws will promptly be fixed by our service team in any place designated or new products will be delivered.

Colours (DUPLEX)











DUPLEX System

The combination of the zinc coating and a layer of structural polyester powder paint guarantee a resistant protection surface, which durability can be defined as a doubled product of the sum of these two coatings.

Production method

laser-cut rings

rings welded in MAG / TIG technology

all the elements are hot dip zinc coated

powder coated rings (DUPLEX system)

Safety

rubber gasket on each rings

no sharp edges

heavy and stable

high resistance to vandalism

can be fixed to the ground

Copyright © 2013 Terra. All rights reserved.






H2400

Standing flowerbed







B front view


2 SETS PACKED IN A BOX


UP TO 5 SETS FOR A EURO PALLET

Set contents

Lower pan with legs		1 item	Mast (profile 50x50 mm)		1 item
Rings		11 items	Mast (profil 60x60 mm)		1 item
Screw 10x50		18 items	Upper span		4 items
Screw 10x90	>	8 items	Lower span	>	4 items
Gasket		38 m	Protective flat bar	>	2 items
Glue for the gasket		4 items			

Additional accessories





number of lines in the system: 6

type of connector: GEKA

flow of drippers: 2-3 l/h

opening pressure of the anti-drip: 0,4 atm

closing pressure of the anti-drip: 0,2 atm

hose type: new generation

resistant to chemicals and acidification

Copyright © 2013 Terra. All rights reserved.



