W600/3 ½

Hanging Flower Tower



Specification

В

BEWARE OF IMITATIONS!

It is impossible to copy quality and safety. Only branded products with the sign of Terra can provide the highest quality, safety and accuracy of workmanship.



Bottom diameter



A 1	Upper diameter of 1st level	•	600 mm
A 2	Upper diameter of 2nd level		500 mm

400 mm **A**3 Upper diameter of 3rd level 400 mm

C Total height 475 mm

D 60 mm Inner radius Ē Inner diameter 120 mm

Radius of 1st level 30 mm


Number of rings 31 I Capacity of substrate

Second bottom capacity

9 kg Weight before planting 22-45 kg Weight of the planting

10-14 items Estimated amount of seedlings

Weightdependsonthetypeofsoilanditsmoisture



Terra Flower Tower construction is under a 2-year warranty program called "DOOR TO DOOR". In fact, it is an extensive system of support and technical assistance, as well as an extremely efficient service guarantee. When a fault is detected in our products, service team fix it wherever you want or exchange the product with a new one.

Production method

laser-cut rings


front view

MAG/TIG welded rings

hot dip galvanized

powder coated rings (DUPLEX system)

Colours



DUPLEX System

The combination of a galvanized layer and a polyester powder coat gives an extraordinary resistance. The top coat of paint, which supposed to be a decoration, becomes an additional anticorrosive layer.

Safety

rubber seals on each ring no sharp edges high weight and stability high resistance to vandalism **Assembly** system






W600/3 ½


Hanging Flower Tower



Transport

side view front view





Set contents

wall fixing	A	(below 59 mm)
	B	(60 - 89 mm)
A rubber ga	asket	2,5 m
Fixing	1 pcs	
Expansion I	2 pcs	
Screw cove	r	3 pcs

Additional Accessories

